


DIRECT FIX CEILING PROPERTIES (DOMESTIC APPLICATIONS)

NAIL UP BATTEN (NUB)							
 <p>To be fixed with either screws or nail up batten clips. Nail fixing of batten not recommended.</p>	DIMENSIONS				Maximum allowable spans		
	"A"	"B"	"C"	BMT	SPACING	SPAN	Max. plaster thickness
	35	16	5	0.5mm	450 600	1200 1100	10 & 13 13
Standard Lengths: 4.8m / 6.0m				The above are for 2 or more continuous spans. For thicker plaster refer to manufacturer.			

PROPERTIES									
Area A_g mm ²	I_x mm ⁴	I_y mm ⁴	Z_x mm ³	Z_y mm ³	r_x mm	r_y mm	J mm ⁴	I_w mm ⁴	F_y mPa
35,756	1.00E+03	8.00E+03	123	419	6.3	14.5	7529	0	300

250

200

150

100

50

SCALE

	BRYKO PTY.LTD. MANUFACTURERS OF METAL BUILDING PRODUCTS ACN 007 251 256				BRYKO PRODUCT SPECIFICATION AND INSTALLATION GUIDE		DRAWN L.C.	CHECKED V.L.	DATE 22.03.2024
	9 PATRICK STREET, CAMPBELLFIELD PH. (03) 9357 0843 FAX. (03) 9357 9204		A NO.	FINAL DRAFT ISSUE AMENDMENT	L.C. DRAWN	22.03.2024 DATE	DRAWING NO. S405		REV. A